

PN:
ANCHOR2WAYSEAM



• Fall Protection • Competent Training • Netting • PPE

Phone: (504) 733-1808
Fax: (504) 733-2996
PalmerSafetyUS.com

TECHNICAL SPECIFICATIONS

2-Way Standing Seam Anchor

The Palmer Safety 2-Way Standing Seam Anchor is lightweight, reusable, and easy-to-use. This product possesses an all steel construction with galvanized finish making it very durable. Compatible with a variety of standing seam designs.

The 2-Way Standing Seam Anchor may be used in Personal Fall Arrest and Restraint applications ONLY:

- Personal Fall Arrest: 2-Way Standing Seam Anchor may be used to support a MAXIMUM 1 PFAS for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', or up to 12' if used in combination with equipment explicitly certified for such use. Applicable D-ring: Dorsal.
- Restraint: 2-Way Standing Seam Anchor may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

Features & Benefits:

- Easy to install
- Lightweight and durable
- Fits wide range of standing seam roofs. See instructions.

WORKER CAPACITY RANGE: 130 -310 lbs.

MATERIAL: Zinc Plated Steel

MIN. BREAKING STRENGTH: 5,000 lbs.

CONFORMS TO: Compliant with all OSHA 1910, 1926 Subpart M, ANSI Z359.18-2017 and ANSI A10.32-2012 regulations. Minimum Service temp: -30°F Type A Anchorage Connector.

